



# De-oxidising gel IF 930

INTERFLUX®  
ELECTRONICS N.V.



Ver.: 2.1 30-05-13

Ver.: 2.1 30-05-13

Page 1



## More information:

Packaging

P.2

## De-oxidising gel for wettable solder nozzles

### Description:

The Interflux® **IF 930** de-oxidising gel is designed to remove oxides from wettable solder nozzles of selective soldering equipment.

IF **930** is applied to the selective soldering nozzle. By purging the solder through the nozzle the oxides are washed off.

IF **930** is succeeding the IF 920



## Applying the product

For best results the **IF 930** should be applied directly from the syringe through a metal needle into the wettable solder nozzle.

Let the IF 930 work for a few seconds before purging the wettable nozzle with solder.

### Physical and chemical properties:

Specific density	: 1.20 g/ml ± 0.1
Colour	: White / yellow
Odour	: mild
pH	: 3
Viscosity	: 250.000 cps
Solubility in water	: insoluble

### Key advantages:

- Easy applicable
- Efficient cleaning action
- Environmental friendly formulation



## Packaging:

IF 930 is available in the following packages:

### Package

5cc syringe with and without plunger

10cc syringe with and without plunger

30cc syringe with and without plunger

Trade name : De-oxidising gel IF 930

D i s c l a i m e r

Because Interflux® Electronics N.V. cannot anticipate or control the many different conditions under which this information and our products may be used, we do not guarantee the applicability or the accuracy of this information or the suitability of our products in any given situation. Users of our products should make their own test to determine the suitability of each such product for their particular purposes. The product discussed is sold without such warranty, either express or implied.

Copyright:

**INTERFLUX®** ELECTRONICS

Please consult the latest  
version of this document  
on:

[www.interflux.com](http://www.interflux.com)

This document in another  
language?:

[www.interflux.com](http://www.interflux.com)