
Conformal Coatings

Technical Data Sheet





PTH

Polyurethane Thinners

PTH is a high purity solvent blend designed for use with Electrolube's polyurethane based conformal coating, PUC. The primary use of PTH is to dilute the coating for use in dip and spray coating applications.

Approvals RoHS-2 Compliant (2011/65/EU): Yes

Liquid Properties Appearance: Clear, colourless liquid

 Density @ 20°C (g/ml):
 0.79

 Flash Point:
 39°C

 VOC Content:
 100%

DescriptionPackagingOrder CodeShelf LifePolyurethane Thinners5 Litres BulkPTH05L36 Months

Directions for Use

Spray Coating

The optimum viscosity to give coating quality and thickness depends on the spray equipment and conditions, as well as the conformal coating chosen. Suitable spray viscosity is typically 50-80mPa s. In addition, extra solvent may need to be added to avoid immediate drying during application, commonly known as 'cobwebbing'. The thinned solution should be stirred thoroughly and allowed to stand. All air bubbles must be allowed time to disperse before attempting to spray. Thinners should be added gradually until the desired spray pattern and coating weight is achieved.

Dip Coating

PTH may be used to maintain the viscosity of PUC conformal coating in open tanks used in dip coating processes. Over time, the solvent within the coatings evaporates. This increases the viscosity and produces a thicker coating. This solvent loss must be replaced to maintain the correct viscosity and provide an economical coating thickness. The amount of PTH to be added depends on the total volume of the tank, ambient temperature and rate of use. PTH should be added slowly, allowing the viscosity of the coating to alter prior to adding additional thinners. PTH is a flammable solvent blend and should be used in a well-ventilated area. All sources of ignition must be avoided. Please refer to the separate Health & Safety Data Sheet for further details.

Equipment Cleaning

PTH thinners may also be used to clean metal equipment found in the coating process including but not limited to, spray guns, dip coating machines.

Revision 1: Oct 2013

Copyright Electrolube 2013

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

Ashby Park, Coalfield Way, Ashby de la Zouch, Leicestershire LE65 1JR T +44 (0)1530 419 600 F +44 (0)1530 416 640 BS EN ISO 9001:2008 Certificate No. FM 32082