AUTOTRONIK

Fertigungssysteme für die Elektronikindustrie

AUTOTRONIK-SMT GmbH


Sulzbacher Str. 111 D-92224 Amberg

Tel +49 (0) 9621-600 691 Fax +49 (0) 9621-600 692

office@autotronik-smt.com www.autotronik-smt.de

MODEL: BA392P1-V

SMT-PICK&PLACE MACHINE





- High Accuracy and high Flexibility from 01005 up to 0.3 mm fine pitch
- ▶ 160 intelligent Auto Tape Feeder
- Ballscrews in X-Y direction
- ► AC-Servo Motors in X/Y/Z
- ▶ Up to 4.500 CPH
- COGNEX Alignment System "Vision On the Fly"
- Bottom Vision Kamera for fine pitch QFP & BGA
- ▶ Automatic Reference Point Recognition
- Conveyor System
- Vision Inspection
- Universal CAD Conversion
- Barcode Reader for Feeder setup





Innovative Features



table



Vorldwide or you!



Specialist in smal and medium-size manufacturing.



innovation a fair price.



one hand







MODEL: BA392P1-V

SMT-PICK&PLACE MACHINE

SPEZIFICATION:

- Number of Heads (Vision on the Fly): 1
- Placement rate (under optimum condition):
 4500 CPH, 3400 CPH (IPC 9850)
- Feeder capacity (8mm): up to 160 Tape Feeders
- IC Tray capacity: up to 4 Waffle Trays
- Component Sense: Vision detection
- Component Size:

Handled by head camera:

- smallest: 0.6 x 0.3 mm
- largest: 16 x 14 mm

Handled by fixed Bottom Vision Camera:

- smallest: 0.4 x 0.2 mm (option)
- largest: 150 x 100 mm
- Resolution:
 - X/Y Axis: 0.005 mm
 - Z Axis: 0.01 mm
- Rotation: 0° to 360° (0.09°/step)
- Placement Accuracy: +/- 0.03 mm
- X/Y Repeatability: +/- 0.01 mm
- Placement Area without conveyor:
 - without Waffle Tray: 600 x 350 mmwith 1 Waffle Tray: 600 x 330 mm
- Placement Area with conveyor:
 - without Waffle Tray: 650 x 315 mmwith 1 Waffle Tray: 650 x 300 mm
- Programming:
 - Direct Input
 - Teach-In by Camera
 - CAD Access (option)
 - Barcode Reader (option)
- Industrial PC with Windows 10
- Power Supply: 230VACPower: 2400W
- Pressure: 75 psi (5.5 bar), max. 100L/min
 Machine Size: 1185 x 1190 x 1350 mm (L x W x H)
- Weight: 810kg







